

PERRY JOHNSON LABORATORY ACCREDITATION, INC.

Certificate of Accreditation

Perry Johnson Laboratory Accreditation, Inc. has assessed the Laboratory of:

TECNOCREO S.r.l

Via Girolamo Savonarola 15, 54033 Carrara (MS), Italy

(Hereinafter called the Organization) and hereby declares that Organization is accredited in accordance with the recognized International Standard:

ISO/IEC 17025:2017

This accreditation demonstrates technical competence for a defined scope and the operation of a laboratory quality management system (as outlined by the joint ISO-ILAC-IAF Communiqué dated April 2017):

Acoustical Testing (As detailed in the supplement)

Accreditation claims for such testing and/or calibration services shall only be made from addresses referenced within this certificate. This Accreditation is granted subject to the system rules governing the Accreditation referred to above, and the Organization hereby covenants with the Accreditation body's duty to observe and comply with the said rules.

For PJLA:

Liacy Szuszen

Tracy Szerszen President

Perry Johnson Laboratory Accreditation, Inc. (PJLA) 755 W. Big Beaver, Suite 1325 Troy, Michigan 48084 Initial Accreditation Date: Issue Date: Expiration Date: April 6, 2022 May 5, 2022 August 31, 2024 Accreditation No.: Certificate No.: 114622 L22-351

The validity of this certificate is maintained through ongoing assessments based on a continuous accreditation cycle. The validity of this certificate should be confirmed through the PJLA website: <u>www.pjlabs.com</u>



Certificate of Accreditation: Supplement

TECNOCREO S.r.l

Via Girolamo Savonarola 15, 54033 Carrara (MS), Italy Contact Name: Dott. Fabrizio Brozzi Phone: 0585 -1812375 Accreditation is granted to the facility to perform the following testing:

FIELD OF TEST	ITEMS, MATERIALS OR PRODUCTS TESTED	SPECIFIC TESTS OR PROPERTIES MEASURED	SPECIFICATION, STANDARD METHOD OR TECHNIQUE USED	RANGE (WHERE APPROPRIATE) AND DETECTION LIMIT
Acoustical ^{FO}	Dispositivi per la riduzione del rumore da traffico stradale Road traffic noise reducing devices	Dispositivi per la riduzione del rumore da traffico stradale - Metodo di prova per la determinazione della prestazione acustica - Parte 5: Caratteristiche intrinseche - Valori in sito della riflessione sonora in condizioni di campo sonoro diretto Road traffic noise reducing devices - Test method for determining the acoustic performance - Part 5: Intrinsic	UNI EN 1793- 5:2016	100 Hz to 5 kHz
		characteristics - In situ values of sound reflection under direct sound field conditions Dispositivi per la riduzione del rumore da traffico stradale - Metodo di prova per la determinazione della prestazione acustica - Parte 6: Caratteristiche intrinseche - Valore in sito di isolamento acustico per via aerea in condizioni di campo sonoro diretto		
		Road traffic noise reducing devices - Test method for determining the acoustic performance - Part 6: Intrinsic characteristics - In situ values of airborne sound insulation under direct sound field conditions		

1. The presence of a superscript FO means that the laboratory performs testing of the indicated parameter both at its fixed location and onsite at customer locations. Example: Outside Micrometer^{FO} would mean that the laboratory performs this testing at its fixed location and onsite at customer locations.